

AEFF、AEVF 特性表

Character List

符合IEC34, CNS 10919 C3192

(220V 3Ø 60Hz)

Output 輸出			Frame No. 框號	Insulating Type 絕緣等級	Full Load Character 滿載特性				Starting Character 起動特性		Max. Torque 最大轉矩	Interia 轉子慣量
馬力 HP	功率 KW	轉速 RMP			Torque 轉距Kg-m	Efficiency 效率%	Power Factor 功率因數%	Current Amp.電流	Torque 轉距%	Current Amp.電流	%	Kg-m ²
1/4	0. 185(0.2)	3335	63	F	0.054	61.0	77.0	1.0	400	6	300	0. 002
		1650	63	F	0. 110	66.0	70.0	1.0	280	6	250	0. 003
		1120	71	F	0. 162	64.0	60.0	1.3	200	6	250	0. 006
1/2	0. 37(0.4)	3370	71	F	0.108	75.0	86.0	1.5	340	12	290	0. 0025
		1680	71	F	0. 216	70.0	75.0	1. 9	200	12	250	0. 005
		1130	80	F	0.321	68.0	67.0	2.2	200	12	230	0. 009
1	0. 75	3395	80	F	0.214	77.0	87.0	2. 9	220	19	280	0. 005
		1700	80	F	0.427	76.0	76.5	3. 4	230	19	280	0. 009
		1140	90L	F	0. 637	76.0	71.0	3.6	200	19	230	0. 018
2	1. 5	3415	90L	F	0.425	80.0	89.0	5.5	250	40	280	0. 011
		1710	90L	F	0.849	79.0	81.0	6.1	220	40	280	0. 018
		1140	100L	F	1.273	78.0	74.0	6.8	180	40	220	0. 033
3	2. 2	3450	90L	F	0.631	82.0	89.0	8.0	250	68	280	0. 015
		1725	100L	F	1.262	82.0	82.5	8.7	210	68	260	0. 033
		1150	112M	F	1.894	82.0	77.0	9.3	180	68	230	0.060
5	3. 7	3450	112M	F	1. 046	84.5	90.0	12.0	240	110	280	0.039
		1745	112M	F	2. 080	85.0	85.0	13.5	220	110	260	0.060
		1150	132S	F	3. 129	84.0	77.0	15.1	180	110	230	0. 154
7 1/2	5.5	3490	132S	F	1. 560	85.0	90.0	19.2	220	160	260	0. 066
		1750	132M	F	3.111	87.0	84.0	20.1	220	160	250	0. 106
		1160	132M	F	4. 693	85.0	77.5	22.3	200	160	230	0. 222
10	7.5	3490	132S	F	2. 080	86.5	90.0	25.1	200	200	210	0. 078
		1750	132M	F	4.148	88.5	88.0	25.1	220	200	250	0. 146
		1170	160M	F	6.204	87.0	80.0	28.1	220	200	230	0. 048
15	11	3510	132M	F	3.102	88.0	90.0	37.1	210	290	240	0. 164
		1760	160M	F	6.186	90.0	89.0	36.7	200	290	250	0. 322
		1170	160L	F	9.306	89.5	84.0	39.1	220	290	230	0. 599
20	15	3520	160M	F	4.124	89.5	91.0	48.1	210	360	240	0. 191
		1760	160L	F	8.428	90.5	86.0	50.3	200	360	240	0. 412
		1170	180M	F	12.408	90.0	85.0	51.2	220	360	210	1. 007
25	18.5	3520	160L	F	5.155	90.0	89.5	60.8	200	440	230	0. 247
		1765	180M	F	10.281	91.0	85.5	62.9	200	440	240	0. 624
		1170	180L	F	15.510	90.0	84.5	64.4	210	440	210	1. 170
30	22	3520	180M	F	6.186	90.5	90.0	72.1	200	550	230	0. 315
		1765	180L	F	12.338	91.5	88.0	72.9	210	550	240	0. 671
		1170	180L	F	18.612	91.0	84.0	76.8	200	550	210	1. 365
40	30	3520	180L	F	8.248	90.5	91.0	95.1	180	620	210	0. 373
		1760	200L	F	16.497	92.0	88.0	96.7	210	620	230	0. 829
		1170		F	24.816	92.0	85.0	100.1	190	620	200	1. 952

AEFF/AEVF series with class F insulation.

Note: 1.Examination method according to CNS 10919 and C3192. 2. The above mentioned value subject to change without notice.